



BSU3 – Adjustable 70A Battery Support Unit



DIAGNOSTICS, RE-PROGRAMMING, ABS BRAKE BLEEDING

BSU3 provides a selectable stable voltage and up to 70 amps of fully regulated power to prevent loss of charge and damage to the battery

BSU3 can be used with any 12v automotive battery.

When the battery is charged the BSU is a regulated power supply to sustain accessory loads and offset parasitic drain.

Can be used in the showroom to maintain the battery charge while power consuming accessories are being demonstrated without fear of power loss.

Reverse polarity protection.

Supplied with 5M IEC power lead.

FEATURES

BSU3 provides a constant voltage to prevent loss of data and possible damage to control units during software updates, and module reprogramming as well as diagnostic processes when in a Key On, Engine Off state.

Output voltage can be selected from one of three preset levels:

12.7V, 13.8V, 14.8V

During diagnostic or programming operations, the vehicle's systems are operating solely from the battery. Maintaining battery charge during this process is critical.

The status of **BSU3** is indicated simply by three LED's – POWER, POLARITY, DEMAND. When all 3 are illuminated, **BSU3** is supporting the battery.

Designed to be wall or ramp mounted the **BSU3** has been designed to meet the needs of the high power consuming vehicle.

SPECIFICATION

Input	100VAC – 240VAC
Output	12.7 – 14.8V up to 70A continuous
Weight	2.1 Kg
Size	298 x 148 x 115 mm