



12/24 VOLT DUO CHARGING SYSTEM

The **Duo Charge** will correctly charge the two batteries of a 24v system, saving month and extended battery life.

In use, the two 12v batteries that make up a 24v system discharge and charge at uneven rates, which results in loss of capacity and early failure.

The **Duo Charge** assesses each battery individually and applies the correct charge to each battery, maximizing

battery life and reliability.

The **Duo Charge** does this without the need to remove or disconnect the batteries. It takes no longer to set up than a conventional 24v charger, and because it assesses the batteries individually it can take less time to fully charge both batteries.

FEATURES

- Patented Sulphation Recovery Program
- Short circuit shutdown without blown fuse
- Reverse polarity protection
- Soft start current control
- Fast constant current bulk charge
- 3-stage charging: CI-CV-Float
- Constant voltage float/standby
- Proportional timing – minimal gas emission
- Independent overrun timer
- Accurate zero-crossing voltage sensing
- Flexibility – to match battery specification
- Available in UK/Euro/110 versions
- Optional trolley available

DUO CHARGE
12V / 24V 10A

DUO BATTERY CHARGER

SPECIFICATIONS

INPUT

100-240VAC
50/60HZ

OUTPUT

2X 12v 10A

WEIGHT

23KG EXCLUDING TROLLEY



SIZE

380 x 265 x 215MM
EXCLUDING TROLLEY

MANUFACTURING ORIGIN

UK

TRACTION DIRECT,
ROUNDWAY MILL,
BUSINESS CENTRE,
DEVIZES,
WILTSHIRE
SN10 2LT

+44 (0)1380 738950
SALES@TRACTION-DIRECT.COM
TRACTION-DIRECT.CO.UK