



12/24 VOLT DUO CHARGING SYSTEM

The Duo Charge will correctly charge the two batteries of a 24v system, saving month and extended battery life.

In use, the two 12v batteries that make up a 24v system discharge and charge at uneven rates, which results in loss of capacity and early failure.

The Duo Charge assesses each battery individually and applies the correct charge to each battery, maximizing

battery life and reliability.

The Duo Charge does this without the need to remove or disconnect the batteries. It takes no longer to set up than a conventional 24v charger, and because it assesses the batteries individually it can take less time to fully charge both batteries.

FEATURES

- Patented Sulphation Recovery Program
- Short circuit shutdown without blown fuse
- Reverse polarity protection
- Soft start current control
- Fast constant current bulk charge
- 3-stage charging: CI-CV-Float
- Constant voltage float/standby
- Proportional timing – minimal gas emission
- Independent overrun timer
- Accurate zero-crossing voltage sensing
- Flexibility – to match battery specification
- Available in UK/Euro/110 versions
- Optional trolley available

DUO CHARGE
12V / 24V 10A

BATTERY CHARGER

SPECIFICATIONS

INPUT

100-240VAC
50/60HZ

OUTPUT

2X 12v 10A

WEIGHT

23KG EXCLUDING TROLLEY



SIZE

380 x 265 x 215MM
EXCLUDING TROLLEY

MANUFACTURING ORIGIN

UK

TRACTION DIRECT,
ROUNDWAY MILL,
BUSINESS CENTRE,
DEVIZES,
WILTSHIRE
SN10 2LT

+44 (0)1380 738950
SALES@TRACTION-DIRECT.COM
TRACTION-DIRECT.CO.UK