



**FOLDING ROOFS, HIGH POWER  
HIFI, AUTO TAILGATE DEMOS**

**SSU2-50B** provides a stable voltage and up to 50 amps of fully regulated power to prevent loss of charge and damage to the battery.

**SSU2-50B** can be used with any 12V automotive battery including AGM and GEL.

When the battery is charged the SSU is a regulated power supply to sustain accessory loads and offset parasitic drain.

Battery state detection, ensuring safe prolonged use.

Output current display.

Reverse polarity protection.

Disconnect detection.

Supplied with 5M IEC power lead and 3M output leads.

**FEATURES**

This low profile (90mm) battery conditioner has been designed specifically for car showrooms.

Most conventional battery conditioners simply trickle charge the battery after it has been drained. The **SSU2-50B** provides instant support to the battery negating the need for recharging.

With the **SSU2-50B** showroom conditioner connected to your vehicles you can be sure that they are always ready for demonstration and that the battery will be kept in prime condition.

This unit has been designed to slip under most vehicles without scratching the floor surface and features automatic current

sensing so that it knows when it is needed.

The intelligent sensing in the **SSU2-50B** determines exactly when support is required to minimize unnecessary noise and power consumption.



**SSU2**  
**50A**

**SHOWROOM  
SUPPORT UNIT**

**SPECIFICATIONS**

**INPUT**

**100-240VAC**  
**50/60HZ**

**SIZE**

**280 x 190 x 90MM**

**CARTON**

**320 x 250 x 230MM**

**OUTPUT**

**13.4v UP TO 50A**  
**CONTINUOUS**

**FORMAT**

**AVAILABLE IN UK, EU, AU AND US  
MAINS INPUT LEAD VARIANTS**

**WEIGHT**

**6KG**

**MANUFACTURING ORIGIN**

**UK**

**TRACTION DIRECT,  
ROUNDWAY HILL  
BUSINESS CENTRE,  
DEVIZES,  
WILTSHIRE  
SN10 2LT**

**+44 (0)1380 738950  
SALES@TRACTION-DIRECT.COM  
TRACTION-DIRECT.CO.UK**