



The **SSU** range have been designed specifically for car showrooms. The chargers all provide a constant voltage to prevent loss of charge and damage to the battery.

Most conventional battery conditioners simply trickle charge the battery after it has been drained. The SSU range provides instant support to the battery negating the need for recharging.

With the **SSU** range connected to your vehicles you can be sure that they are always ready for demonstration and that the battery will be kept in prime condition.

The units have been designed to slip under most vehicles without scratching the floor surface and features automatic current sensing so that it knows when it is needed. An expanding range of adapters are also available to allow simple connection directly to the vehicle battery or via distribution points. **OEM approved:**



## SSU2-25



INPUT  
**100-240VAC**  
**50/60HZ**

OUTPUT  
**13.4v UP TO 25A**  
CONTINUOUS

WEIGHT  
**2.5KG**

SIZE  
**280 x 130 x 90MM**  
CARTON  
**320 x 250 x 230MM**

## SSU2-50B



INPUT  
**100-240VAC**  
**50/60HZ**

OUTPUT  
**13.4v UP TO 25A**  
CONTINUOUS

WEIGHT  
**2.5KG**

SIZE  
**280 x 190 x 90MM**  
CARTON  
**320 x 250 x 230MM**

All Traction Showroom Support Units are manufactured at their own site in Devizes, UK.

TRACTION DIRECT,  
ROUNDWAY HILL BUSINESS CENTRE,  
DEVIZES, WILTSHIRE SN10 2LT

**+44 (0)1380 738950**  
[UK.SALES@TRACTION-DIRECT.COM](mailto:UK.SALES@TRACTION-DIRECT.COM)  
[TRACTION-DIRECT.CO.UK](http://TRACTION-DIRECT.CO.UK)

# SHOWROOM

# SUPPORT UNIT RANGE