



The **SSU** range have been designed specifically for car showrooms. The chargers all provide a constant voltage to prevent loss of charge and damage to the battery.

Most conventional battery conditioners simply trickle charge the battery after it has been drained. The SSU range provides instant support to the battery negating the need for recharging.

With the **SSU** range connected to your vehicles you can be sure that they are always ready for demonstration and that the battery will be kept in prime condition.

The units have been designed to slip under most vehicles without scratching the floor surface and features automatic current sensing so that it knows when it is needed. An expanding range of adapters are also available to allow simple connection directly to the vehicle battery or via distribution points. **OEM approved:**



SSU2-25



INPUT
100-240_{VAC}
50/60_{Hz}

OUTPUT
13.4_v UP TO 25_A
CONTINUOUS

WEIGHT
2.5_{KG}

SIZE
280 x 130 x 90_{MM}
CARTON
320 x 250 x 230_{MM}

SSU2-50B



INPUT
100-240_{VAC}
50/60_{Hz}

OUTPUT
13.4_v UP TO 25_A
CONTINUOUS

WEIGHT
2.5_{KG}

SIZE
280 x 190 x 90_{MM}
CARTON
320 x 250 x 230_{MM}

All Traction Showroom Support Units are manufactured at their own site in Devizes, UK.

TRACTION CHARGER,
ROUNDWAY HILL BUSINESS CENTRE,
DEVIZES, WILTSHIRE SN10 2LT

+44(0)330 022 7822
SALES@TRACTIONCHARGER.COM
TRACTIONCHARGER.COM

SHOWROOM SUPPORT UNIT RANGE